What is claimed is: Claims

1(currently amended). A support for a shower head (8) having, comprising:

1.1 a mounting fixture (2) for mounting the support such that the support is

adjustable, latter may be adjusted, if desired,

 $\frac{4.2}{4.2}$ an arm $\frac{(5, 15)}{15}$ jutting out of the mounting fixture $\frac{(2)}{15}$,

1 1 1

- a receptacle $\frac{(16)}{(16)}$ for a shower head $\frac{(8)}{(16)}$ arranged in the vicinity of the far end of the arm $\frac{(5, 15)}{(16)}$, and
- $\frac{4.4}{1.4}$ at least one additional shower fixture $\frac{(41)}{1.4}$ attached to the arm $\frac{(5, 15)}{1.4}$.

2(currently amended). A shower support according to claim 1, wherein the additional shower fixture (11) may can be supplied with water independently of the shower head (8).

3(currently amended). A shower support according to claim 1 or claim 2, having a channel passing through the arm (5, 15) and leading to the additional shower fixture (11).

4(currently amended). A shower support according to <u>claim 1</u> any of the <u>foregoing claims</u>, wherein the arm (5, 15) is <u>configured in the form of comprises</u> a length of hollow, profiled stock, at least out <u>from the mounting fixture</u> to the additional shower fixture (11).

5(currently amended). A shower support according to <u>claim 1</u> any of the foregoing claims, wherein the additional shower fixture (11) is arranged between the mounting fixture (2) and the far end of the arm (5, 15).

6(currently amended). A shower support according to <u>claim 1 any of the</u> foregoing claims, wherein <u>a the</u> direction of <u>a the</u> jet exiting the additional shower fixture (11) is adjustable.

7(currently amended). A shower support according to <u>claim 1</u> any of the <u>foregoing claims</u>, wherein the additional shower fixture (11) is mounted on <u>a</u> the side of the <u>wall-mounting</u> arm (5, 15) jutting from the mounting fixture.

8(currently amended). A shower support according to <u>claim 1 any of the</u>

foregoing claims, wherein at least one <u>said</u> additional shower fixture (11) is mounted
on <u>a the</u> underside of the <u>wall-mounting</u> arm (5, 15) <u>jutting from the mounting fixture</u>.

9(currently amended). A shower support according to <u>claim 1</u> any of the <u>foregoing claims</u>, having several additional <u>said</u> shower fixtures (11) and a water-supply conduit common to all <u>the</u> additional shower fixtures (11).

10(currently amended). A shower support according to <u>claim 1</u> any of the foregoing claims, wherein the additional shower fixture (11) is nondetachable.

11(currently amended). A shower support according to <u>claim 1 any of claims</u> 1 - 9, wherein at least one additional shower fixture (11) is attached to the arm (5, 15) by means of a quick-connect coupler.

12(currently amended). A shower support according to <u>claim 1</u> any of the foregoing claims, wherein the arm (5, 15) is pivotable about a horizontal axis orthogonal to <u>a its</u> longitudinal axis <u>of the arm,</u> on a linkage on the mounting fixture (2).

13(original). A shower support according to claim 12, wherein the water conduit passes through the linkage.

14(currently amended). A shower support according to <u>claim 1</u> any of the foregoing claims, wherein the arm (5, 15) is configured in the form of a fork.

15(currently amended). A shower support according to claim 14, wherein the additional shower fixtures (11) are arranged on the outer faces of the tines (14) of the fork.

16(currently amended). A shower support according to <u>claim 1</u> any of the <u>foregoing claims</u>, wherein the shower head (8) is detachable.

17(currently amended). A shower support according to <u>claim 1</u> any of the <u>foregoing claims</u>, wherein the shower head (8) is supplied with water by a hose (10).